



PCB Layout (Top View)

MATERIALS :

1. INSULATOR : Thermoplastic (UL 94V-0), Black.
2. CONTACT : Sq. 0.50mm Copper Alloy, Gold Plated.

SPECIFICATION

1. CURRENT RATING : 1.0 AMP. Max.
2. DIELECTRIC WITHSTAND VOLTAGE : 800V AC R.M.S. For 60 Seconds.
3. INSULATION RESISTANCE : 1,000M Ohms Min. At 500V DC
4. OPERATING TEMPERATURE : -55°C to +105°C.



Order Information	Pos.	Dimension			Order Information	Pos.	Dimension		
		A	B	C			A	B	C
HA12R-06	06	13.20	12.10	4.00	HA12R-28	28	35.20	34.10	26.00
HA12R-08	08	15.20	14.10	6.00	HA12R-30	30	37.20	36.10	28.00
HA12R-10	10	17.20	16.10	8.00	HA12R-32	32	39.20	38.10	30.00
HA12R-12	12	19.20	18.10	10.00	HA12R-34	34	41.20	40.10	32.00
HA12R-14	14	21.20	20.10	12.00	HA12R-36	36	43.20	42.10	34.00
HA12R-16	16	23.20	22.10	14.00	HA12R-40	40	47.20	46.10	38.00
HA12R-18	18	25.20	24.10	16.00	HA12R-44	44	51.20	50.10	42.00
HA12R-20	20	27.20	26.10	18.00	HA12R-50	50	57.20	56.10	48.00
HA12R-22	22	29.20	28.10	20.00	HA12R-60	60	67.20	66.10	58.00
HA12R-24	24	31.20	30.10	22.00	HA12R-64	64	71.20	70.10	62.00
HA12R-26	26	33.20	32.10	24.00	HA12R-68	68	75.20	74.10	66.00

CONWIN ENTERPRISES CO., LTD.

禧司康有限公司

No. 25, Lane 372, Jinmen St., Ban Chiao 22071, Taipei, Taiwan
 TEL: 886-2-2675-3311 FAX: 886-2-2675-0501

TITLE	2.00mm Box Header Right Angle Type	APP.BY	H.H.T.-09/13/08'	TOLERANCE UNLESS OTHERWISE SPECIFIED	SIZE:	A4
PART No:	HA12R-** Series	CHK.BY	Natalia-09/13/08'	LINEAR	0.0 ±0.38	SHEET: 1/1
DRW No:	HA12R001SP	DRW.BY	Natalia-09/13/08'		0.00 ±0.25	COMMENTS:
PROJECT:	UNIT: mm	SCALE	NOT TO SCALE	ANGLES	±3°	